

SAFETY DATA SHEET

1. Identification

Product identifier Selenium Bronze Alloys

Other means of identification

SDS number 10

Product code C89510, C89520, Se-Bi-Alloy

Recommended useManufacturing **Recommended restrictions**Not assigned.

Manufacturer / Importer / Supplier / Distributor information

Address 131 Myoma Road (PO Box 816) Mars, PA 16046

Telephone 1-800-626-7071

E-mail dpl@concast.com or adk@concast.com

Contact person Dominic LeMaire or Andy Krowsoski

Emergency phone number 1-800-424-9300

Chemtrec (24-hrs)

Company name Concast Metal Products Company

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSensitization, skinCategory 1

Carcinogenicity Category 2
Specific target organ toxicity, repeated Category 2

exposure

OSHA hazard(s) Not classified.

Label elements

Hazard symbol



Signal word Warning

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer. May cause damage to organs

(Lung) through prolonged or repeated exposure by inhalation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Use personal protective equipment as required. Contaminated work clothing

should not be allowed out of the workplace. Do not breathe fumes and dusts.

Response If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse. If exposed or concerned: Get medical

advice/attention. Get medical advice/attention if you feel unwell.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

Environmental hazards Hazardous to the aquatic environment, Category 3

long-term hazard

3. Composition/information on ingredients

Mixture

Hazardous components

Chemical name	Common name and	CAS number	%
	synonyms		
Copper		7440-50-8	85 - 88
Tin		7440-31-5	4 - 6

Selenium Bronze Alloys SDS US

Chemical name	Common name and synonyms	CAS number	
Zinc		7440-66-6	4 - 6
Selenium		7782-49-2	0.35 - 1.1
Nickel	7440-02-0		0 - 1
Lead		7439-92-1	0 - 0.25

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The alloy contains additional alloying elements at concentrations below disclosure requirements. At temperatures above the melting point the alloys may liberate fumes containing oxides of alloying elements.

4. First-aid measures

Inhalation

In case of exposure to fumes or particulates: Move to fresh air. Get medical attention if discomfort

persists.

Skin contact

Contact with dust: Wash skin with soap and water. In case of allergic reaction or other skin disorders: Seek medical attention and bring along these instructions. In case of contact with hot or molten product, cool rapidly with water and seek immediate medical attention. Do not attempt to remove molten product from skin because skin will tear easily. Cuts or abrasions should be treated promptly with thorough cleansing of the affected area.

Eye contact

Do not rub eyes. Remove any contact lenses. Flush eyes thoroughly with water, taking care to rinse under eyelids. If irritation persists, continue flushing for 15 minutes, rinsing from time to time under eyelids. If discomfort continues, consult a physician.

May cause skin and eye irritation. May cause irritation to mucous membranes. Cough. Shortness

Ingestion

Rinse mouth thoroughly if dust is ingested. Only induce vomiting at the instruction of medical

personnel. Get medical attention if any discomfort continues.

Most important

symptoms/effects, acute and

delayed

Treat symptomatically. Symptoms may be delayed.

of breath. Wheezing. Sensitization.

Indication of immediate medical attention and special treatment needed

General information

Get medical attention if any discomfort develops. Seek medical attention for all burns, regardless how minor they may seem. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Special powder against metal fires. Dry sand.

Do not use water or halogenated extinguishing media. Do not use water on molten metal: Explosion hazard could result.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Solid metal is not flammable; however, finely divided metallic dust or powder may form an explosive mixture with air. In a fire, nickel may form nickel carbonyl, a highly toxic substance and known carcinogen.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire-fighting equipment/instructions

Move containers from fire area if you can do it without risk.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation. Avoid inhalation of dust and contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

Methods and materials for containment and cleaning up

Avoid dust formation. Allow spilled material to solidify and scrape up with shovels into a suitable container for recycle or disposal. Collect dust using a vacuum cleaner equipped with HEPA filter. The vacuum cleaner should be explosion-proofed. If not possible, gently moisten dust before it is collected with shovel, broom or the like. This material and its container must be disposed of as hazardous waste.

Environmental precautions

Avoid release to the environment. Do not contaminate water.

Selenium Bronze Alloys SDS US

7. Handling and storage

Precautions for safe handling

Welding, burning, sawing, brazing, grinding or machining operations may generate fumes and dusts of metal oxides. Provide adequate ventilation. Avoid contact with sharp edges and hot surfaces. Avoid inhalation of dust and contact with skin and eyes. Avoid generation and spreading of dust and fumes. Avoid contact with hot or molten material. Dust clouds may be explosive under certain conditions. Take precautionary measures against static discharges when there is a risk of dust explosion. Use explosion-proof electrical equipment if airborne dust levels are high. To prevent and minimize fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system. Wear appropriate personal protective equipment. Do not use water on molten metal. Do not eat, drink or smoke when using the product. Keep the workplace clean. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep dry. Store away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	Value	
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.	1000)	
Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	PEL	0.5 mg/m3	
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
Selenium (CAS 7782-49-2)	PEL	0.2 mg/m3	
Tin (CAS 7440-31-5)	PEL	2 mg/m3	
US. ACGIH Threshold Limit Values	5		
			_

Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	TWA	0.5 mg/m3	
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Lead (CAS 7439-92-1)	TWA	0.05 mg/m3	
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
Selenium (CAS 7782-49-2)	TWA	0.2 mg/m3	
Tin (CAS 7440-31-5)	TWA	2 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form
Antimony (CAS 7440-36-0)	REL	0.5 mg/m3	
Copper (CAS 7440-50-8)	REL	1 mg/m3	Dust and mist.
Lead (CAS 7439-92-1)	REL	0.05 mg/m3	
Nickel (CAS 7440-02-0)	REL	0.015 mg/m3	
Selenium (CAS 7782-49-2)	REL	0.2 mg/m3	
Tin (CAS 7440-31-5)	REL	2 mg/m3	

Biological limit values

US. ACGIH. BEIs. Biological Exposure Indices

Components Value D	erminant Sampling Time
ead (CAS 7439-92-1) 300 μg/l L	* t

^{* -} For sampling details, please see the source document.

Exposure guidelines

Follow standard monitoring procedures.

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of dust. Ventilate as needed to control airborne dust. Use explosion-proof ventilation equipment if airborne dust levels are high. Special ventilation should be used to convey finely divided metallic dust generated by grinding, sawing etc., in order to eliminate explosion hazards.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear dust-resistant safety goggles where there is danger of eye contact. In addition to safety glasses or goggles, a welding helmet with appropriate shaded shield is required during welding, burning, or brazing. A face shield is recommended, in addition to safety glasses or goggles, during sawing, grinding, or machining.

Selenium Bronze Alloys SDS US

Skin protection

Hand protection Wear suitable protective gloves to prevent cuts and abrasions. When material is heated, wear

gloves to protect against thermal burns. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory equipment

with particle filter. When engineering controls are not sufficient to lower exposure levels below the applicable exposure limit, use a NIOSH approved respirator for dusts. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever work place conditions warrant a respirator's use. Seek advice from local supervisor.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated uniforms should be laundered separately from other clothing to prevent potential cross-contamination. If possible, an industrial laundry service should be used to eliminate the possibility of contaminating the home environment. Handle in accordance with good industrial hygiene and safety practices. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance Shapes, Solids, Tubes & Turnings.

Physical state Solid.

Form Shapes, Solids, Tubes & Turnings.

Color Yellow. Odor None.

Odor threshold Not available. Not available. pН Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Not available. Flash point Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Vapor pressure Not available. Not available. Vapor density

4 28 Relative density

Not soluble in water. Solubility(ies)

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Viscosity

10. Stability and reactivity

Reactivity Not available.

Chemical stability Stable at normal conditions. Massive metal is stable and non reactive under normal conditions of

use, storage and transport.

Possibility of hazardous

reactions

Hazardous polymerization does not occur. Hot molten material will react violently with water

resulting in spattering and fuming.

Conditions to avoid Contact with incompatible materials. Contact with acids will release flammable hydrogen gas.

Avoid dust formation. Dust clouds may be explosive under certain conditions.

Incompatible materials Acids. Ammonium nitrate. Fluoride. Halogens. Nitrates. Phosphorus. Strong oxidizing agents.

Sulfur.

Selenium Bronze Allovs SDS US 4/8

Hazardous decomposition

Welding, burning, sawing, brazing, grinding or machining operations may generate dusts and fumos of motal oxides. Phosphorus oxides. Salonium exides.

products fumes of metal oxides. Phosphorus oxides. Selenium/selenium oxides.

11. Toxicological information

Information on likely routes of exposure

Ingestion Not relevant, due to the form of the product. However, ingestion of dusts generated during

working operations may cause nausea and vomiting.

Inhalation Elevated temperatures or mechanical action may form dust and fumes which may be irritating to

the mucous membranes and respiratory tract. In sensitized individuals, exposure causes an

asthma-like attack, with wheezing, bronchospasm, and dyspnea.

Skin contact May cause an allergic skin reaction. Hot or molten material may produce thermal burns. Workers

allergic to nickel may develop eczema or rashes. Acute exposure to cobalt metal, dust, and fume may cause irritation of skin and eyes. In sensitized individuals, exposure causes an asthma-like

attack, with wheezing, bronchospasm, and dyspnea.

Eye contact Molten material will produce thermal burns. Elevated temperatures or mechanical action may form

dust and fumes which may be irritating to the eye.

Symptoms related to the physical, chemical and toxicological characteristics

May cause irritation to mucous membranes. May cause skin and eye irritation. Coughing.

Wheezing. Shortness of breath. Sensitization.

Information on toxicological effects

Acute toxicity High concentrations of freshly formed fumes/dusts of metal oxides can produce symptoms of

metal fume fever. Acute exposure to dust, and fume may cause irritation of skin and eyes. In sensitized individuals, exposure causes an asthma-like attack, with wheezing, bronchospasm,

and dyspnea.

Skin corrosion/irritation Elevated temperatures or mechanical action may form dust and fumes which may be irritating to

the eye, mucous membranes and respiratory tract. Hot or molten material may produce thermal

burns

Serious eye damage/eye

irritation

Dust from machining operation in the eyes may cause irritation.

Respiratory sensitization Not classified.

Skin sensitization Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

May cause sensitization by skin contact. Pre-existing skin conditions including dermatitis might be

aggravated by exposure to this product.

Germ cell mutagenicity No data available.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Lead (CAS 7439-92-1) 2B Possibly carcinogenic to humans.

Nickel (CAS 7440-02-0) 1 Carcinogenic to humans.

Selenium (CAS 7782-49-2) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Nickel (CAS 7440-02-0) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Causes damage to the following organs through prolonged or repeated exposure: Lung.

Aspiration hazard Not available.

Chronic effects Harmful: danger of serious damage to health by prolonged exposure through inhalation. Chronic

Nickel: Has shown teratogenic effects in laboratory animals.

inhalation of high concentrations of iron oxide fumes or dust may lead to benign pneumoconiosis (siderosis). Prolonged and repeated overexposure to dust and fumes can lead to benign pneumoconiosis (stannosis). Chronic inhalation of metallic oxide dust/fume may cause metal

fume fever.

Further information Welding or plasma arc cutting of metal and alloys can generate ozone, nitric oxides and ultraviolet

radiation. Ozone overexposure may result in mucous membrane irritation or pulmonary

discomfort. UV radiation can cause skin erythema and welders flash.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Selenium Bronze Alloys SDS US

Components Species Test Results

Antimony (CAS 7440-36-0)

Aquatic

Fish LC50 Sheepshead minnow (Cyprinodon 6.2 - 8.3 mg/l, 96 hours

variegatus)

Lead (CAS 7439-92-1)

LC50 Rainbow trout, donaldson trout 1.17 mg/l, 96 Hours

(Oncorhynhus mykiss)

Selenium (CAS 7782-49-2)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 0.94 - 1.2 mg/l, 96 hours

Bioaccumulative potentialThe product contains potentially bioaccumulating substances.Mobility in soilAlloys in massive forms are not mobile in the environment.Mobility in generalAlloys in massive forms are not mobile in the environment.

Other adverse effects An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

13. Disposal considerations

Disposal instructionsThis material and its container must be disposed of as hazardous waste. Dispose in accordance

with all applicable regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code Z110: Inorganic compounds n.o.s.

Waste from residues / unused

products

Recover and recycle, if practical. Solid metal and alloys in the form of particles may be reactive. Its hazardous characteristics, including fire and explosion, should be determined prior to disposal.

Contaminated packaging Not applicable.

14. Transport information

DOT

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

IMDG

Not regulated as a dangerous good.

Transport in bulk according to

No information available.

Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Lead (CAS 7439-92-1) 29 CFR 1910.1025

CERCLA Hazardous Substance List (40 CFR 302.4)

Antimony (CAS 7440-36-0) LISTED
Copper (CAS 7440-50-8) LISTED
Lead (CAS 7439-92-1) LISTED
Nickel (CAS 7440-02-0) LISTED
Selenium (CAS 7782-49-2) LISTED
Zinc (CAS 7440-66-6) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

No

SARA 311/312 Hazardous

Yes

chemical

Selenium Bronze Alloys SDS US

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Antimony (CAS 7440-36-0) Lead (CAS 7439-92-1)

Nickel (CAS 7440-02-0)

Selenium (CAS 7782-49-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Not listed

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Not regulated.

DEA Exempt Chemical Mixtures Code Number

Not regulated.

Food and Drug

Not regulated.

Administration (FDA)

US state regulations

WARNING: This product may contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Antimony (CAS 7440-36-0)

Copper (CAS 7440-50-8)

Lead (CAS 7439-92-1)

Nickel (CAS 7440-02-0)

Selenium (CAS 7782-49-2)

Tin (CAS 7440-31-5)

Zinc (CAS 7440-66-6)

US. New Jersey Worker and Community Right-to-Know Act

Antimony (CAS 7440-36-0)	500 LBS
Copper (CAS 7440-50-8)	500 LBS
Lead (CAS 7439-92-1)	500 LBS
Nickel (CAS 7440-02-0)	500 LBS
Selenium (CAS 7782-49-2)	500 LBS
Zinc (CAS 7440-66-6)	500 LBS

US. Pennsylvania RTK - Hazardous Substances

Antimony (CAS 7440-36-0)

Copper (CAS 7440-50-8)

Lead (CAS 7439-92-1)

Nickel (CAS 7440-02-0)

Selenium (CAS 7782-49-2)

Tin (CAS 7440-31-5) Zinc (CAS 7440-66-6)

US. Rhode Island RTK

Antimony (CAS 7440-36-0)

Copper (CAS 7440-50-8)

Lead (CAS 7439-92-1)

Nickel (CAS 7440-02-0)

Selenium (CAS 7782-49-2)

Tin (CAS 7440-31-5)

Zinc (CAS 7440-66-6)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Lead (CAS 7439-92-1) Nickel (CAS 7440-02-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Selenium Bronze Alloys SDS US

Country(s) or region Inventory name On inventory (yes/no)* European Inventory of Existing Commercial Chemical Europe Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

Philippine Inventory of Chemicals and Chemical Substances

16. Other information, including date of preparation or last version

Issue date 11-05-2012

Revision date Version # 01

Philippines

Further information Not available.

References HSDB® - Hazardous Substances Data Bank

> IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

Disclaimer The information in this MSDS was obtained from industry sources that we believe to be reliable.

However, the information is provided without any representation or warranty, expressed or implied regarding the accuracy or correctness. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with the handling, storage, use, or disposal of

Yes

8/8

the product.

Selenium Bronze Allovs SDS US

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)